

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 192 911 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

03.04.2002 Bulletin 2002/14

(51) Int Cl.7: A61B 17/70

(21) Application number: 01122510.9

(22) Date of filing: 21.09.2001

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 22.09.2000 JP 2000289291

(71) Applicant: Showa IKA Kohgyo Co., Ltd.

Aichi-ken (JP)

(72) Inventors:

- Sato, Shigenobu
Sapporo-shi, Hokkaido (JP)

• Nohara, Yutaka

Koshigaya-shi, Saitama-ken (JP)

• Oribe, Kazuya, Showa Ika Kohgyo Co., Ltd.

Minato-ku, Tokyo (JP)

• Takamido, Hiroshi, Showa Ika Kohgyo Co., Ltd.

Nagoya-shi, Aichi-ken (JP)

(74) Representative: HOFFMANN - EITLE

Patent- und Rechtsanwälte


Arabellastrasse 4

81925 München (DE)

(54) Bone connecting tool and connecting member thereof

(57) In a bone connecting tool comprising a rod connecting member 5 attachable to an arch of vertebrae 3 in a corpus vertebrae 1, and a rod member 9 having a rod portion 7 freely fixed to the rod connecting member 5, wherein a projection portion 23 for eating into the arch of vertebrae 3 is provided in a second hook portion 13 provided in the rod connecting member 5, the rod member 9 is provided with a processus spinosus 27 in the corpus vertebrae 1 or a first hook portion 25 freely hooked to the arch of vertebrae 3 in one end portion thereof, and a projection portion 29 for eating into the processus spinosus 27 or the arch of vertebrae 3 is provided in the first hook portion 25. The rod member 9 and 31 are formed in a substantially J shape or a substantially V shape, and a projection portion 37 eating into the processus spinosus 27 is provided inside a bent portion 35.

FIG.1



EP 1 192 911 A2

Description

BACKGROUND OF THE INVENTION

Field of the invention

[0001] The present invention relates to a bone connecting tool for connecting a corpus vertebrae and a connecting member used in the bone connecting tool, and more particularly to a bone connecting tool which can properly and stably keep a positional relationship between the corpus vertebrae and the connecting tool, and a connecting member thereof.

Description of the Related Art

[0002] In the case of connecting a corpus vertebrae such as a lumbar vertebrae or the like, there is executed a method of screwing and inserting respective screws to apart bodies of vertebrae in a corpus vertebrae, respectively engaging one end side and another end side of a rod with engagement grooves formed in a head portion of the respective screws and fixing both end sides of the rod to both screws by a fixing screw. Further, there is employed a structure of supporting and fixing both end portions of the rod by a hook member provided with a hook portion freely hooked to an arch of vertebrae in the corpus vertebrae.

[0003] In the structure of screwing and inserting the screws to the bodies of vertebrae in the corpus vertebrae and supporting both end portions of the rod by the screws, it is necessary to screw and insert the screw to the corpus vertebrae in an accurate direction and at an accurate depth, so that there is a problem that it is hard to screw and insert the screw.

[0004] In the structure of hooking the hook portion of the hook member to the arch of vertebrae in the corpus vertebrae and supporting and fixing both end portions of the rod by the respective hook member, it is unnecessary to screw and insert the screw to the corpus vertebrae. However, since the hook portion in the hook member is simply hooked to the arch of vertebrae, there is a problem to be improved in view of improving a stability.

SUMMARY OF THE INVENTION

[0005] The present invention is made by taking the problems described above into consideration, according to a first aspect of the present invention, there is provided a bone connecting tool for interconnecting vertebral bodies comprising: a rod engaging member attachable to an arch of vertebrae in a corpus vertebrae; and a rod member having a rod portion freely fixed to the rod engaging member, wherein a projection portion for eating into the arch of vertebrae is provided in the second hook portion provided in the rod engaging member.

[0006] Moreover, the structure may be made such

that the rod member is provided with a processus spinosus in the corpus vertebrae or a first hook portion freely hooked to the arch of vertebrae in one end portion thereof, and a projection portion for eating into the processus spinosus or the arch of vertebrae is provided in the first hook portion.

[0007] Moreover, there is provided a bone connecting tool comprising: a hook member freely hooked to an arch of vertebrae in a corpus vertebrae; and a connecting member having a rod portion freely fixed to the rod engaging member, wherein the rod member is provided with a processus spinosus in the corpus vertebrae or a first hook portion freely hooked to the arch of vertebrae in one end portion thereof, and a projection portion for eating into the processus spinosus or the arch of vertebrae is provided in the first hook portion.

[0008] Moreover, the rod member in the structure described above is structured so as to have a substantially V shape or J shape, and is provided with a projection portion inside a bent portion.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009]

Fig. 1 is a schematic view showing a use example of a bone connecting tool according to a first embodiment of the present invention;

Fig. 2 is a perspective explanation view of the bone connecting tool described above; and

Fig. 3 is a perspective explanation view showing a second embodiment of a connecting member according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0010] Hereinafter, a description of embodiments according to the present invention will be given with reference to the accompanying drawings.

<First embodiment>

[0011] Fig. 1 is a view showing a first embodiment according to the present invention. A bone connecting tool for interconnecting vertebral bodies is provided with a rod members 9 and 11 having a rod engaging member 5 freely mounted to an arch of vertebrae 3 in a corpus vertebrae 1 and a rod portion 7 freely fixed to the rod engaging member 5. The rod engaging member 5 is, as shown in Fig. 2, provided with a curved second hook portion 13 freely hooked to the arch of vertebrae 3 and a rod fixing portion 15 freely fixing the rod portions 7 of the rod members 9 and 11.

[0012] More particularly, the rod fixing portion 15 is provided with an engagement groove 17 freely engaging the rod portions 7 of the rod members 9 and 11. A screw portion 21 screwing a fixing screw 19 which freely

presses and fixes the rod portion 7 engaged with the engagement groove 17 in an immobile state is formed in both sides of the engagement groove 17.

[0013] The second hook portion 13 is integrally provided in the rod fixing portion 15 in an opposite side in an opening direction of the engagement groove 17 and the screw portion 21 (on a back surface in the case that the engagement groove 17 is a front surface), and a center in a width direction of the second hook portion 13 coincides with a center in a width direction of the engagement groove 17. A projection portion 23 for eating into the arch of vertebrae 3 of the corpus vertebrae is formed in a center portion in the width direction of the second hook portion 13.

[0014] It is sufficient that the projection portion 23 has a function of eating into the arch of vertebrae 3 at a time of hooking the second hook portion 13 to the arch of vertebrae 3, for example, the projection 23 may be an acanthous projection, however, in the present embodiment, is formed as a linear protrusion along a curve of a curved inner surface 13a in the second hook portion 13. In this case, in the illustrated embodiment, the projection portion 23 is exemplified by one protrusion, however, a plurality of protrusions may be employed, or an inclined protrusion or a plurality of crossed protrusions may be employed, so that various kinds of structures can be employed as an aspect of the projection portion 23.

[0015] The rod member 9 is, as shown in Fig. 2, structured such as to be provided with the rod portion freely engaging with the engagement groove 17 of the rod engaging member 5 in one end portion, and provided with a first hook portion 25 in another end portion, and is schematically formed in a substantially J shape. The first hook portion 25 is curved so as to be hooked to the arch of vertebrae 3 in the corpus vertebrae 1 or the processus spinosus 27 (refer to Fig. 1), and a projection portion 29 is provided on a curved inner surface 25a of the first hook portion 25 in the same manner as the second hook portion 13 in the rod engaging member 5. Since it is sufficient that the projection portion 29 has the same structure as that of the projection portion 23 of the second hook portion 13, a detailed description thereof will be omitted.

[0016] Since the rod member 11 shown in Fig. 1 is a simple linear rod engaged with and supported to the engagement groove 17 in the rod engaging member 5 at both end portions, a detailed description thereof will be omitted.

[0017] In the structure described above, as shown in Fig. 1, it is possible to integrally bond and connect the corpuses vertebrae 1 apart from each other by the rod engaging member 5 and the rod member 9 by hooking the second hook portion 13 of the rod engaging member 5 to the arch of vertebrae 3 in one corpus vertebrae, hooking the first hook portion 25 in the rod member 9 to the processus spinosus 27 in another corpus vertebrae apart therefrom, engaging the rod portion 7 of the rod

member 9 with the engagement groove 17 of the rod engaging member 5 and pressing and fixing by the fixing screw 19, and it is possible to prevent the corpuses vertebrae 1 from moving in an apart direction to each other. In addition, the diameter of the rod portion 9 is smaller than the width of the engagement groove 17. So, the rod member 11 can rotate the inside of the engagement groove 17 freely until it fixes a rod portion 9 with the fixing screw 19.

[0018] When hooking the second hook portion 13 in the rod engaging member 5 to the arch of vertebrae 3 in the corpus vertebrae in the manner as described above, the projection portion 23 provided in the second hook portion 13 eats into the arch of vertebrae 3 described above, and when hooking the first hook portion 25 of the rod member 9 to the processus spinosus 27, the projection portion 23 provided in the first hook portion 25 eats into the processus spinosus 27. Accordingly, it is possible to stably mount the rod engaging member 5 with respect to a fixed position of the arch of vertebrae 3 in an immobile state, and it is possible to stably mount the first hook portion 25 of the rod member 9 with respect to a predetermined position of the processus spinosus 27. That is, at a time of connecting the apart corpuses vertebrae to each other, it is possible to easily and stably execute the operation by the rod engaging member 5 and the rod member 9.

[0019] In the case of using the rod member 11, as shown in Fig. 1, the apart corpuses vertebrae 1 are connected by hooking the second hook portions 13 in the respective rod engaging members 5 to the arches of vertebrae 3 in the corpuses vertebrae 1 apart from each other so that a pair of rod engaging members 5 are directed to opposite directions to each other, engaging both end portions of the rod member 11 with the engagement grooves 17 in a pair of rod engaging members 5 and fastening and fixing by the fixing screws 19. In addition, the diameter of the rod portion 9 is smaller than the width of the engagement groove 17. So, the rod portion 11 can rotate the inside of the engagement groove 17 freely until it fixes a rod portion 9 with the fixing screw 19.

[0020] At this time, the rod member 11 functions so as to protrude, and can prevent the corpuses of vertebrae 1 apart from each other from moving in a direction moving close to each other. In this case, the projection portion 23 provided in the second hook portion 13 in the rod engaging member 5 eats into the arch of vertebrae 3, and keeps a stable state.

<Second embodiment>

[0021] Fig. 3 is a view showing a second embodiment according to the present invention. This embodiment is constituted by a rod member 31 formed in a substantially V shape or the like. The rod member 31 is provided with rod portions 33a and 33b corresponding to the rod portion 7 in the rod member 9 in both sides of a bent portion

35 so as to be formed in a U shape or a V shape, and is structured such as to be provided with a projection portion 37 corresponding to the projection portion 29 inside the bent portion 35.

[0022] A portion near a front end portion of each of the rod portions 33a and 33b in the rod member 31 is engaged with the engagement groove 17 of the rod engaging member 5 in the same manner as that of the rod portion 7 of the connecting member 9, and fixed by the fixing screw 19. In the case that the rod engaging member 5 can not be mounted to the arch of vertebrae 3 in the corpus vertebrae, the structure can be made such that the screw is screwed and inserted to the corpus vertebrae in the same manner as that of the conventional one and the portion near the front end portion of each of the rod portions 33a and 33b in the rod member 31 is fixed by a head portion of the screw.

[0023] The structure is made such that the rod member 31 is formed in the U shape or the V shape as described above and both end portions of the rod member 31 are fixed by the rod engaging member 5, the screw or the like, whereby the rod member 31 can be stably and firmly fixed and it is possible to properly and securely keep the positional relationship between the corpus vertebrae and the bone connecting tool.

Claims

1. A bone connecting tool for interconnecting vertebral bodies comprising:

a rod member having a first hook portion;
a rod engaging member fixed to the rod member having a second hook portion,

wherein

a projection portion for eating into an arch of vertebrae is provided in the second hook portion.

2. A bone connecting tool for interconnecting vertebral bodies according to claim 1, wherein the first hook portion having a projection portion, the projection portion is eaten into the processus spinosus in the corpus vertebrae or the arch of vertebrae, is provided in one end of said rod member.

3. A bone connecting tool for interconnecting vertebral bodies comprising:

a rod engaging member attachable to an arch of vertebrae in a corpus vertebrae; and
a rod member having a rod portion freely fixed to the rod engaging member, wherein the rod member is provided with a processus spinosus in the corpus vertebrae or a hook portion freely hooked to the arch of vertebrae in one end portion thereof, and a projection por-

tion for eating into the processus spinosus or the arch of vertebrae is provided in the hook portion.

4. A bone connecting tool for interconnecting vertebral bodies according to claim 1, 2 or 3, wherein the rod member has a substantially J-shape having a bent portion and a projection portion is provided inside the bent portion.

5. A bone connecting tool for interconnecting vertebral bodies according to claim 1, 2 or 3, wherein the rod member has a substantially V-shape having a bent portion and a projection portion is provided inside the bent portion.

6. A rod member used for connecting vertebral bodies, wherein the rod member is formed in a substantially V shape and is provided with a projection portion eaten into a processus spinosus inside a bent portion.

7. A rod member used for connecting vertebral bodies, wherein the rod member is formed in a substantially J shape and is provided with a projection portion eaten into a processus spinosus inside a bent portion.

8. A bone connecting tool for interconnecting vertebral bodies according to any one of the preceding claims, wherein the projection portion of the rod engaging member is constituted by at least one groove of protrusion.

9. A bone connecting tool for interconnecting vertebral bodies according to any one of the preceding claims, wherein the rod engaging member comprises:

a fixing screw;
a screw portion with which the fixing screw is screwed; and
an engagement groove communicating with the screw portion, wherein
a rod portion of the rod member is inserted to the engagement groove and the rod is pressed and fixed by the fixing screw.

10. A rod engaging member used for connecting vertebral bodies, wherein the rod engaging member comprises:

a rod fixing portion;
a curved hook portion integrally formed in the rod fixing portion; and
a projection portion provided in the hook portion, wherein
the projection portion eats into the arch of ver-

tebrae at a time of hooking the hook portion to the arch of vertebrae.

11. A bone connecting tool for interconnecting vertebral bodies according to claim 9, wherein a diameter of the rod portion is smaller than a width of the engagement groove.

5

10

15

20

25

30

35

40

45

50

55

5

FIG.1




FIG.2






FIG.3





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 192 911 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
29.01.2003 Bulletin 2003/05

(51) Int Cl.7: A61B 17/70

(43) Date of publication A2:
03.04.2002 Bulletin 2002/14

(21) Application number: 01122510.9

(22) Date of filing: 21.09.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- Nohara, Yutaka
Koshigaya-shi, Saitama-ken (JP)
- Oribe, Kazuya, Showa Ika Kohgyo Co., Ltd.
Minato-ku, Tokyo (JP)
- Takamido, Hiroshi, Showa Ika Kohgyo Co., Ltd.
Nagoya-shi, Aichi-ken (JP)

(30) Priority: 22.09.2000 JP 2000289291

(71) Applicant: Showa IKA Kohgyo Co., Ltd.
Aichi-ken (JP)


- (74) Representative: Schuster, Thomas, Dipl.-Phys.
Grünecker, Kinkeldey, Stockmair &
Schwanhäusser
Anwaltssozietät
Maximilianstrasse 58
80538 München (DE)

(72) Inventors:
• Sato, Shigenobu
Sapporo-shi, Hokkaido (JP)

(54) Bone connecting tool and connecting member thereof

(57) In a bone connecting tool comprising a rod connecting member 5 attachable to an arch of vertebrae 3 in a corpus vertebrae 1, and a rod member 9 having a rod portion 7 freely fixed to the rod connecting member 5, wherein a projection portion 23 for eating into the arch of vertebrae 3 is provided in a second hook portion 13 provided in the rod connecting member 5, the rod member 9 is provided with a processus spinosus 27 in the corpus vertebrae 1 or a first hook portion 25 freely hooked to the arch of vertebrae 3 in one end portion thereof, and a projection portion 29 for eating into the processus spinosus 27 or the arch of vertebrae 3 is provided in the first hook portion 25. The rod member 9 and 31 are formed in a substantially J shape or a substantially V shape, and a projection portion 37 eating into the processus spinosus 27 is provided inside a bent portion 35.

FIG.1



EP 1 192 911 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 2510

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 395 370 A (MUELLER WALTER ET AL) 7 March 1995 (1995-03-07)	1-4,7,8,10	A61B17/70
Y	* column 4, line 35 - line 47; figure 2 *	5,6,9,11	
Y	US 5 725 582 A (BEVAN DAVID ROBIN ET AL) 10 March 1998 (1998-03-10)	5,6	
A	* abstract; figures 7,11,16 *	1,3,7,10	
Y	US 5 520 689 A (FLUECKIGER MARKUS ET AL) 28 May 1996 (1996-05-28)	9,11	
A	* abstract; figure 1 *	1,3,7,10	
A	US 5 306 275 A (BRYAN DONALD W) 26 April 1994 (1994-04-26)	1,3,5-7,10	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 743 045 A (GAZZANI ROMOLO IGINO ;SHABOLDO OLEG PAVLOVICH (RU)) 20 November 1996 (1996-11-20)	1,3,5-7,10	
A	US 6 077 263 A (AMEIL MARC ET AL) 20 June 2000 (2000-06-20)	1,3,7,9-11	
	* abstract; figure 1 *		A61B
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 10 December 2002	Examiner Hansen, S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 2510

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

10-12-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5395370	A	07-03-1995	CH	686610 A5	15-05-1996
			AT	133325 T	15-02-1996
			CA	2080869 A1	19-04-1993
			DE	59205155 D1	07-03-1996
			EP	0537598 A2	21-04-1993
US 5725582	A	10-03-1998	CA	2142836 A1	03-03-1994
			DE	69323636 D1	01-04-1999
			DE	69323636 T2	01-07-1999
			EP	0768843 A1	23-04-1997
			ES	2129522 T3	16-06-1999
			WO	9404088 A1	03-03-1994
			GB	2269753 A ,B	23-02-1994
			JP	8502668 T	26-03-1996
US 5520689	A	28-05-1996	US	6077262 A	20-06-2000
			CA	2097623 A1	05-12-1993
			DE	59301618 D1	28-03-1996
			EP	0572790 A1	08-12-1993
			ES	2085673 T3	01-06-1996
			JP	2561611 B2	11-12-1996
			JP	6030950 A	08-02-1994
US 5306275	A	26-04-1994	US	5498262 A	12-03-1996
			US	5947965 A	07-09-1999
EP 0743045	A	20-11-1996	RU	2078551 C1	10-05-1997
			RU	2089124 C1	10-09-1997
			RU	2113186 C1	20-06-1998
			EP	0743045 A2	20-11-1996
			EP	0873718 A2	28-10-1998
US 6077263	A	20-06-2000	FR	2767263 A1	19-02-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82